

Product Overview

The 'RX' Running Tool is designed to set X, XN, R, RN, and RQ locking mandrels in corresponding X, XN, R, RN, and RQ landing nipples. It is generally used for installing safety valves in the uppermost landing nipple. The tool allows the lock mandrel to be run with its keys in either the **control or locating position**. A snap ring provides a positive indication when the lock mandrel is fully set.

Key Features

- Sets X, XN, R, RN, and RQ locking mandrels.
- Compatible with corresponding X, XN, R, RN, and RQ landing nipples.
- Suitable for **safety-valve installation** in the uppermost landing nipple.
- Lock mandrel keys can be positioned in **control or locating positions**.
- Keys provide the **no-go locating function** for the nipple when applicable.
- For non-no-go locks, the keys are run in the **locating position**.
- **Snap-ring position** gives a positive indication that the lock is fully set.

Technical Data

Nominal Size (in.)	Max. O.D. (in.)	Fishing Neck O.D. (in.)	Top Connection
2.313	2.12	1.750	15/16-10 UN
2.750	2.62	2.313	1-1/16-10 UN
3.125	3.09	2.313	1-1/16-10 UN
3.313	3.09	2.313	1-1/16-10 UN
3.688	3.62	2.313	1-1/16-10 UN
3.813	3.62	2.313	1-1/16-10 UN
4.562	4.50	3.125	1-1/16-10 UN
5.875	5.80	3.125	1-1/16-10 UN
5.963	5.81	3.125	1-1/16-10 UN

